

AT852D

ESD
SAFE

Lead-free & ESD Safe Premium Digital Hot Air Station

Application

- Production line
- Institutes
- Enterprises
- Education and Practice
- Maintenance
- Hobby



Package list	Standard Packing:
Main Unit : 1 PCS	Inner box : 33.5x7.5x20 (CM)
Hot Air Gun: 1 PCS	N.W.: 3.8kgs
Gun Holder: 1 PCS	G.W.: 4.2kgs
AC Cord: 1 PCS	Carton: 6PCS/Carton
Nozzle: 2PCS	Size: 57x35x62 (CM)
Manual: 1PCS	N.W.: 22.5kgs
	G.W.: 23.8kgs

850 Heater



Nozzles



Features:

- Closed-loop and MCU zero crossing design for achieving fast heating-up, accurate and stable control.
- Knob control and LED display make work easy.
- High power diaphragm pump with high pressure make it suitable for various nozzles.
- Patented heater for obtaining fast heating-up and extending lifespan.
- Intelligence cooling system and deferred power-off function to extend handpiece lifespan.

Specification:

Voltage:	AC (100V/110V/120V 220V/230V/240V) 50/60Hz(Optional)
Power consumption:	550W
Temperature range:	100-480°C
Display mode:	LED display
Air flow grades:	A25~A99 grades
Pump	Diaphragm pump
Air flow gradation:	23L/min (MAX)
Noise:	<52dB(A)

Appendix

Nozzles

