



[www.shirtronics.com](http://www.shirtronics.com) :web site  
[info@shirtronics.com](mailto:info@shirtronics.com) :e-mail

שירטרוניקס בע"מ .  
כתובת למשלוח דואר: ת.ד. 437 שמשית 17906 ישראל,  
משרדים+לוג: זרחיר  
טלפון: 04-9938666, פקס: 04-9938777  
עוסק מורשה: 513501064

## Vertical Laminar Flow Cabinet



BBS-DDC/BBS-SDC



BBS-V680



BBS-V800

## TECHNICAL PARAMETERS

Model	BBS-V680 ▶	BBS-V800 ▶	BBS-DDC ▶	BBS-SDC ▶
External Size (W*D*H)	680*410*1160mm	802*650*1550mm	1040*615*1770mm	1440*615*1770mm
Internal Size (W*D*H)	630*375*615mm	800*600*540mm	940*540*545mm	1340*540*545mm
Work Surface Height	/	660mm	750mm	750mm
Display	LED Display			
Airflow Velocity	Average of 0.3~0.5m/s, air speed adjustable.			
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel			
Pre-Filter	Polyester fiber, washable			
HEPA Filter	99.999% efficiency at 0.3 μm			
Noise	<60dB			
Front Window	/	Manual, 5mm toughened glass, anti-UV		
Max Opening	/	490mm	350mm	350mm
Fluorescent Lamp	14W*1	14W*1	21W*1	28W*1
UV Lamp	15W*1	20W*1	18W*1	30W*1
	Emission of 253.7 nanometers			
Consumption	160W	350W	350W	600W
Caster	/	Universal wheel with leveling feet		
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz			
Standard Accessory	Fluorescent lamp, UV lamp*2 ( for all models ) Water & gas tap (for model BBS-V680) Base stand (except model BBS-V680)			
Gross Weight	50kg	116kg	150kg	174kg
Package Size (W*D*H)	840*560*1380 mm	960*800*1800mm	1190*890*1340mm	1590*890*1330mm