




DIGIHELIC® 3 DIFFERENTIAL PRESSURE CONTROLLER

Digihelic® Controller in Photohelic® Gage, Square Root Output for Flow



Scan here
to watch
product video



The **SERIES DH3** Digihelic® Differential Pressure Controller is a 3-in-1 instrument possessing a digital display gage, control relay switches, and a transmitter with current output all packed in the popular Photohelic® gage style housing. Combining these 3 features allows the reduction of several instruments with one product, saving inventory, installation time and money. The Digihelic® controller is the ideal instrument for pressure, velocity and flow applications, achieving a 1% full scale accuracy on ranges down to the extremely low 0.25 in w.c. to 2.5 in w.c. full-scale. Ranges of 5 in w.c. and greater maintain 0.5% FS accuracy. Bi-directional ranges are also available. The Series DH3 Digihelic® controller allows the selection of pressure, velocity or volumetric flow operation in several commonly used engineering units. 2 SPDT control relays with adjustable deadbands are provided along with a scalable 4-20 mA process output.

Programming is easy using the menu key to access 5 simplified menus which provide access to: security level; selection of pressure, velocity or flow operation; selection of engineering units; K-factor for use with flow sensors; rectangular or circular duct for inputting area in flow applications; set point control or set point and alarm operation; alarm operation as a high, low or high/low alarm; automatic or manual alarm reset; alarm delay; view peak and valley process reading; digital damping for smoothing erratic process applications; scaling the 4-20 mA process output to fit your applications range and field calibration.

FEATURES/BENEFITS

- 3-in-1 instrument allows the reduction of several instruments with one product, saving inventory, installation time and money
- Full scale accuracy of 1% even on extremely low ranges, and 0.5% for ranges above 5 in w.c. provide for greater measurement precision
- Secure menu program provides access to device operation only for the right skill level

APPLICATIONS

- SCFM duct flow
- Filter status
- Duct or building static pressure
- Damper and fan control

MODEL CHART					
Model	Ranges	Price	Model	Ranges	Price
DH3-002	0-0.25 in w.c.	\$355.00	*DH3-010	0-50 in w.c.	\$289.00
DH3-003	0-0.5 in w.c.	289.00	*DH3-011	0-100 in w.c.	289.00
DH3-004	0-1 in w.c.	289.00	*DH3-013	0.25-0.25 in w.c.	355.00
DH3-005	0-2.5 in w.c.	289.00	*DH3-014	0.5-0.5 in w.c.	289.00
DH3-006	0-5 in w.c.	289.00	*DH3-015	1-0-1 in w.c.	289.00
DH3-007	0-10 in w.c.	289.00	*DH3-016	2.5-0-2.5 in w.c.	289.00
DH3-009	0-25 in w.c.	289.00	*DH3-017	5-0-5 in w.c.	289.00
			*DH3-018	10-0-10 in w.c.	289.00

*Velocity and volumetric flow not available on bi-directional range units and models DH3-010 and DH3-011.

SPECIFICATIONS

Service: Air and non-combustible, compatible gases.

Wetted Materials: Consult factory.

Housing Material: Die cast aluminum case and bezel.

Accuracy: $\pm 1.5\%$ for 0.25 in and ± 0.25 in w.c. ranges. Ranges 0.5 in to 5 in w.c. and corresponding bi-directional (except ± 2.5 in w.c.) $\pm 1\%$; All other ranges: $\pm 0.5\%$ @ 77°F (25°C) including hysteresis and repeatability (after 1 hour warm-up).

Stability: $< \pm 1\%$ per year.

Pressure Limits: Ranges ≤ 2.5 in w.c.: 25 psi; ± 2.5 , 5 in w.c.: 5 psi; 10 in w.c.: 5 psi; 25 in w.c.: 5 psi; 50 in w.c.: 5 psi; 100 in w.c.: 9 psi.

Temperature Limits: 32 to 140°F (0 to 60°C).

Compensated Temperature Limits: 32 to 140°F (0 to 60°C).

Thermal Effects: 0.020%/°F (0.036/°C) from 77°F (25°C). For 0.25 in and ± 0.25 in w.c. ranges: $\pm 0.03\%/^{\circ}\text{F}$ ($\pm 0.054\%/^{\circ}\text{C}$).

Power Requirements: 12-28 VDC, 12-28 VAC 50 to 400 Hz.

Power Consumption: 3 VA max.

Output Signal: 4-20 mA DC into 900 Ω max.

Zero & Span Adjustments: Accessible via menus.

Response Time: 250 ms (damping set to 1).

Display: Backlit 4 digit LCD 0.4" height LED indicators for set point and alarm status.

Electrical Connections: 15 pin male high density D-sub connection. 18" (46 cm) cable with 10 conductors included. 4' and 10' cables available.

Process Connections: 1/8" female NPT. Side or back connections.

Mounting Orientation: Mount unit in vertical plane.

Size: 5" (127 mm) OD x 3-1/8" (79.38 mm).

Weight: 1.75 lb (794 g).

Agency Approvals: CE.

SWITCH SPECIFICATIONS

Switch Type: 2 SPDT relays.

Electrical Rating: 1 A @ 30 VAC/VDC.

Set Point Adjustment: Adjustable via keypad on face.

ACCESSORIES

Model	Description	Price
A-298	Flat aluminum bracket for flush mounting	\$27.75
A-301	Static pressure tip for 1/4" metal tubing connection	9.90
A-302	Static pressure tip for 3/16" and 1/8" I.D. plastic or rubber tubing	9.10
A-302F-A	303 SS static pressure tip with mounting flange; for 3/16" ID rubber or plastic tubing; 4" insertion depth; includes mounting screws	9.10
A-370	Mounting bracket flush mount bracket; bracket is then surface mounted; steel with gray hammertone epoxy finish	33.75
A-489	4" straight static pressure tip with flange	6.67

OPTIONS

To order add suffix:	Description	Price
-NIST	NIST traceable calibration certificate	\$139.00 ^(N)
Example: DH3-004-NIST		
-FC	Factory calibration certificate	30.00 ^(N)
Example: DH3-004-FC		
^(N) Items are net priced and are not subject to any discount.		

Process Tubing Options: See page 443 (Gage Tubing Accessories)