



WorkSafe® Light CFR

Group 478

An ideal anti-fatigue mat for wet industrial areas, WorkSafe Light has a well-engineered drainage system and molded-in edges provide safe access.

- Lightweight
- High Performance
- Cutting Fluid Resistant
- Overall thickness 1/2"

Categories & Applications Anti-Fatigue Matting

Suitable Environment Wet Area, Dry floors or where oils, hydraulic fluid, most hydrocarbons are commonly present.

Customization Options Standard Sizes Only

Solid or Drainage Drainage

Material Cutting Fluid Resistant Rubber

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Not Available
Temperature Range	10 to 250 F
Coefficient of Friction	ASTM F1677 / Dry: COF = > .90 / Wet: COF = .34
Compression Deflection	ASTM D575 / Deflection @35 psi, mm=4.10
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
478.12x3x10GY	715411536603	Gray	1/2 In. (13 mm)	3' x 10'	Y	EA
478.12x3x20GY	715411536030	Gray	1/2 In. (13 mm)	3' x 20'	Y	EA
478.12x3x5GY	715411538010	Gray	1/2 In. (13 mm)	3' x 5'	Y	EA