



24/Seven® LockSafe® Drainage GR - Interlocking Rubber Floor Tiles 3' x 3'

Group 578-GR

Performance meets comfort. 24/SEVEN LockSafe GR is Grease Resistant, natural rubber ideal for dry areas or areas with primarily water. The open surface is ideal for heavy traffic in dry or wet areas.

These large 3'x3' rubber tiles require no tools for assembly making installation to any configuration quick and easy. Use optional 24/SEVEN GR edging and corners when and where you need them.

The Positive Interlock System provides a secure connection in all directions, so you don't have to worry about them coming apart even with heavy foot traffic. Secure connections, lightweight design, and unmatched flexibility allow assembled sections to be lifted up, rolled up, and rolled away for removal or maintenance. Tiles hold together and only come apart when you want them to.

Can be used in industrial or food and beverage processing and production environments.

- U.S. PATENT NO. D882,293 S
- Large 3 ft x 3 ft tiles
- Available in 2 different rubber compounds based on environmental exposures
 - GR - for water or dry debris or NBR - for petroleum-based fluids
 - Hidden positive interlocking system
 - Choice of [solid](#) or drainage style
 - Create your own custom widths or lengths in 12" (30 cm) increments
 - Overall thickness 5/8" (16 mm)

Learn more about 24/SEVEN LockSafe [here](#).

Categories & Applications Anti-Fatigue Flooring

Suitable Environment	Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner., Wet Area, Slippery
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Material	Grease Resistant Natural Rubber (GR)
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .84 / Wet: COF = .45
Compression Deflection	ASTM D575 - 16.5 psi @ 25% = .13" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
578.58x3x3GRBK	715411703067	Black	5/8 In. (16 mm)	3' x 3'	Y	EA