



24/Seven® WorkStation Nitrile Rubber (NBR) Floor Mat - Drainage

Group 588-NBR

24/Seven Workstation was designed to fit today's demanding workplaces. This drainage mat is the right option in the most rugged environments. Designed for performance and long-term comfort, the built-in yellow safety ramps provide smooth and safe transition on and off. NBR (Nitrile Rubber) compound is best for oily areas, and areas that see petroleum based fluids.

- NBR - Nitrile Rubber
- Bright, built-in safety borders
- Long-term comfort and value
- Overall thickness 5/8" (15.875mm)

Categories & Applications Anti-Fatigue Matting

Suitable Environment

Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner., Wet Area, Dry floors or where oils, hydraulic fluid, most hydrocarbons are commonly present., Slippery

Customization Options

C1 - Standard Sizes

Solid or Drainage

Drainage

Material

Nitrile Rubber (NBR)

Recycled

Warranty

1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 200 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .68
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
588.58X2X3NBRBYL		Black w/Yellow Borders	5/8 In. (16 mm)	2' x 3'	Y	EA
588.58X3X4NBRBYL		Black w/Yellow Borders	5/8 In. (16 mm)	3' x 4'	Y	EA
588.58X3X5NBRBYL		Black w/Yellow Borders	5/8 In. (16 mm)	3' x 5'	Y	EA