



LockSafe Heavy Duty Drainage, NBR Rubber with GRITSHIELD

Group 589

LockSafe Heavy Duty with GRITSHIELD takes slip resistance to the extreme and is the perfect combination of safety, durability, and comfort. The addition of GRITSHIELD provides more traction with a better coefficient of friction.

GRITSHIELD empowers workers to walk with confidence and move in any environment where slips and falls were previously a constant threat.

The surface of the tile features a unique raised cylinder design intermixed with a uniform series of drainage holes- combining excellent slip resistance with industry-leading airflow, drainage, and material pass-through.

The LockSafe Heavy Duty with GRITSHIELD mat is so robust it can even be placed directly over open grating. The patented LockSafe positive interlock system keeps tiles together and is easy to customize on-site to fit your space.

Choose the LockSafe Heavy Duty with GRITSHIELD for unmatched durability, safety, and performance in the slickest areas.

This 3/4 In. (19 mm) thick, 3x3 Ft. (.91x.91 m) interlocking modular tile is built to withstand the harshest and most relentless work conditions.

- Cut lengths are not available for this product
- Full customization available
- Available in 3x3 Ft. (.91x.91 m) interlocking modular tiles. Allows for full do it yourself customization on-site
- Proudly manufactured in North America in Guadalajara, Mexico
- Patent Pending

Categories & Applications

Suitable Environment	Wet Area, Dry floors or where oils, hydraulic fluid, most hydrocarbons are commonly present.
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Material	Nitrile Rubber (NBR)
Recycled	20%
Warranty	1 Year

Property		Test / Result				
Flammability		MVSS 302 / 'A'; Rating				
Taber Abrasion		ASTM D 3884 / 1% loss				
Temperature Range		10 to 140 F				
Coefficient of Friction		ASTM F1677 / Dry: COF = 1.1 / Wet COF = .96				
Compression Deflection		ASTM D575 - 16.4psi @ 25% = .24" distance compressed				
Tear Strength		Not Applicable				
ESD Rating		Not Rated for ESD Applications				
Dielectric Strength		Not Rated for Switchboard Applications				
SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
589.34x3x3NBRBK		Black	3/4 In. (19 mm)		Y	EA