

50601323



Safety cabinet 90 min for lithium batteries High 2 doors

ADVANTAGES

- Storage of flammables
- Storage of lithium-ion fire-stop construction EI180
- Inside to outside batteries
- Tested 105 min - from outside to inside in accordance with standard EN14470-1
- French manufacturing - CSR
- FM compliant
- Fire resistance 90 min - Tested and approved to standard EN 14470-1 and EN 1363-1

BUT ALSO...

- Locking system
- Thermo-expanding of the doors ventilation
- Holes for the seals connection to the
- Reduce the risk of fire and explosion



TECHNICAL FEATURES

		Ventilation	Both inlet and outlet on the top of the cabinet
Doors color	white RAL 9010	Openings diameter (mm)	100
Number of doors	2	Connecting sleeve	1
Doors type	swing doors	Number of compartments	1
Hinges	left and right	HS Code	488.00
Door closure	automatic closing		94032080
Shipping dimensions HxWxD (mm)	2150 x 1200 x 800		

ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

• Perforated shelf for 2-door safety cabinet (Réf : E35LI)	• Containment sump for 2-door cabinets Types 30, 60 & 90 (Réf : B235)	• Perforated cover plate for 2-door safety cabinets Types 30, 60 & 90 (Réf : C235)	• Rack of 9 electrical outlets (Réf : PRISELI)	• Rack of 6 electrical outlets equipped with a thermal-magnetic circuit breaker (Réf : PRISELICC)	• Ventilation box for a connection to the outside (Réf : CDV-A)
• Connecting kit (Réf : PRISELIUK) (Réf : PRISELIF)	• Breakthrough for electrical outlets (UK) (Switzerland) (Réf :)	• Rack of 7 G-type outlets type J (Germany) (Réf : (Réf : PEXTBALI)	• Rack of 8 electrical outlets type F fire-resistant cable	• Rack of 8 electric KRC (Réf : PRISELICH)	

External dimensions Internal dimensions

HxWxD (mm)	HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg) 4	1950 x
1137 x 620	1620 x 1000 x 410	0		4	100	488.00	